

SC-19



A value 19" surveillance display with rapid response time, quick signal-switching and robust video support for security and control centre environments.

For a cost-effective surveillance display solution, look no further than the AG Neovo SC-19. A bright, high resolution full colour screen with quick signal-switching and 3ms response time ensures sharp, smooth video playback. Looping BNC video inputs and NTSC/PAL support maximise flexibility for system integration. And with built-in speakers, stylishly slim profile and VESA mountability, the SC-19 will look just as attractive as its amazingly affordable price.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-19

Specifications		SC-19
Panel	Panel Type	TFT LCD
	Panel Size	19.0" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294 mm
	Brightness	300 cd/m ² (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour	16.7M
	Response Time	3 ms (GTG)
	Panel Life Time	50,000 hrs (Minimum)
Frequency (H/V)		H: 31 kHz - 80 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue	D-Sub via DVI-VGA cable
	Digital BNC Security	29-Pin DVI-I BNC Connector in / out
Audio	Audio In Speaker	3.5 mm Audio Line-in 1W x 2
Power	AC-DC Adaptor Power Consumption	External AC 100-240 V, 50-60 Hz < 36 W (On) < 1.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	-5° ~ +15°
Dimensions	Product (W x H x D)	420 x 408 x 164mm (16.5" x 16.1" x 6.5")
	Packaging (W x H x D)	460 x 460 x 160mm (18.1" x 18.1" x 6.3")
Weight	Product Weight	3.8 kg (8.4 lbs)
	Packaged Weight	5.7 kg (12.5 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, FCC-B, RoHS
Accessories	Supplied	User manual, power cord, power adaptor, DVI-VGA cable, audio cable



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI and BNC In/Out